

Rustins

Wood Primer

Aluminium



STIR WELL BEFORE USE

Rustins Aluminium Wood Primer is an oil based primer containing aluminium pigment which provides better water resistance.

Preparation

Wood should be sanded smooth and any knots sealed with Rustins Knotting. Holes or cracks should be filled with Rustins Wood Filler after priming. Thin if necessary.

Application

Using a brush, apply evenly. For interior use 1 coat may be sufficient, exterior surfaces require 2 coats.

Re-coating Time

Touch-dry in approximately 4 hours, depending upon temperature and humidity. Undercoat may be applied after 12-16 hours.

Coverage

This tin will cover approximately 7 sq.m in 1 coat depending on the absorbency of the surface.

Cleaning

Remove excess product from brushes before cleaning whilst wet with white

spirit or Rustins Brush Cleaner. Hard brushes can be cleaned with Rustins Brush Restorer.

Disposal (pollution prevention)

Some local authorities have special facilities for disposal of waste paints/varnishes /coatings. Do not empty product into drains or watercourses.

Storage

Store in a cool dry place with the lid tightly closed.

HEALTH AND SAFETY Flammable liquid and vapour.

Contains cobalt octoate, methyl ethyl ketoxime. May produce an allergic reaction.

Take precautionary measures against static discharge.

Wear eye protection.

IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.

In case of fire: Use carbon dioxide for extinction.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container to hazardous or special waste collection point.




WARNING

Please refer to Product Data Sheet for full information at www.rustins.co.uk

For information on Rustins' products visit our website at www.rustins.co.uk or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom rustins@rustins.co.uk
Telephone: +44 (0)20 8450 4666



EU Limit value for this product (CAT Ag):
350g/l (2010)
This product contains max 331 g/l VOC



500ml e