

IMPORTANT

Factory pre-sealed cork floor tiles may be wax coated which will affect the drying of Rustin's Polyurethane Floor Sealer. Test on a spare tile or a small area of the floor. If the coating still remains tacky after eight to ten hours the floor should be dewaxed with White Spirit and steel wool, wiping whilst still damp with clean rag.

Rustins' range includes:

- | | |
|--|---------------------------------|
| Acrylic Varnishes | Polyurethane Varnishes |
| Aluminium Paints | Primers |
| Bitumen Black | Quick Drying Coloured Varnishes |
| Black Matt Paint | Radiator Paint |
| Blackboard Black | Rust Remover |
| Brick & Tile Paint | Strypit Paint & Varnish |
| Clear Metal Lacquer for Brass & Copper | Stripper |
| Danish Oil | Teak Oil |
| French Polishes | Wallpaper Remover |
| Gold Paint | Wood Dyes |
| Grainfiller | Woodstopping |
| Knotting | Yacht Varnish |
| Paint, Gloss & Undercoat | |

Contents will cover approximately 35 sq. metres (375 sq. ft.) one coat

World's finest range of products for the professional & home handyman

For information on Rustins' products visit our website at www.rustins.co.uk or contact us at Rustins Ltd, Waterloo Road, London, NW2 7TX United Kingdom rustins@rustins.co.uk Telephone: +44 (0)20 8450 4666



2 1/2 litres e

Rustins

Clear **Polyurethane floor sealer**

gloss finish

for wood and cork

for a perfect seal!



STIR WELL BEFORE USE. IF NOT STIRRED UNTIL THERE IS NO SEDIMENT AT THE BOTTOM OF THE TIN.

Rustins Polyurethane Floor Sealer is a high solid air drying Polyurethane. For use on clean, bare wood, hardboard, MDF and unsealed cork. Three coats are recommended on wood and four on cork floors. It is essential that the floor is thoroughly clean and free from wax and grease. If a floor has previously been waxed, it is advisable to clean the wax off the floor, even if it is to be sanded, otherwise wax can be left on the sanding belt and traces left on the sanded floor. This would then prevent the Polyurethane from drying properly. Wax polish can be removed by rubbing in the direction of the grain with grade 3 or 4 steel wool and White Spirit, wiping off the solution of wax formed with clean rag. If the floor is to be sanded, ensure that all nail heads are punched below the surface before sanding. Nail holes and cracks can be filled with Rustins Wood Filler.

Existing varnish not being removed should be clean and lightly sanded to provide a key. Bare wood or old floors that have been sanded may be stained with Rustins Wood Dye before coating. Other brands of dye may not be compatible.

The Polyurethane Floor Sealer should be applied liberally with the biggest brush available, or with a roller. The drying time is between 4-6 hours, according to temperature.

This tin will cover approximately 35 square metres one coat, depending on porosity of the surface.

Brushes and rollers can be cleaned after use with White Spirit or Rustins Brush Restorer. White Spirit may also be used to thin the Polyurethane Floor Sealer, if required. The sealer may also be used on old concrete to prevent dusting.

HEALTH AND SAFETY

Flammable liquid and vapour.

Contains cobalt octoate, methyl ethyl ketoxime. May produce an allergic reaction.

Repeated exposure may cause skin dryness or cracking.

Take precautionary measures against static discharge.

Wear eye protection.

IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.

In case of fire: Use carbon dioxide for extinction.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container to hazardous or special waste collection point.



WARNING



EU Limit value for the product (CAT A1): 900g/l (2010). This product contains max 480 g/l VOC.

Rustins

Clear **Polyurethane floor sealer**

gloss finish

for wood and cork

for a perfect seal!

