

SAFETY DATA SHEET

Fleetwood Quick Dry Interior Varnish Gloss

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Fleetwood Quick Dry Interior Varnish Gloss

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Paint

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

FSW Coatings Ltd.
Ballaghanea, Virginia,
A82 N267, Co Cavan,
Ireland.
353 49854 7209

E-mail

info@fleetwood.ie

Revision

01/10/2024

SDS Version

2.0

1.4. Emergency telephone number

The National Poisons Information Centre (NPIC)

Public: +353 (0) 1 809 2166 (7 days a week, 8am- 10pm)

Healthcare professionals: +353 (0) 1 809 2566 (24 h service)

See also section 4 "First aid measures"

Emergency contact number (FSW): + 353 49854 7209 (9am - 5pm, Monday - Friday)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Not classified according to Regulation (EC) No. 1272/2008 (CLP).

2.2. Label elements

Hazard pictogram(s)

Not applicable.

Signal word

Not applicable.

Hazard statement(s)

Not applicable.

Precautionary statement(s)

General

-

Prevention

-

Response

-

Storage

-

Disposal

Hazardous substances

None known.

Additional labelling

EUH208, Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 2-methylisothiazol-3(2H)-one. May produce an allergic reaction.

EUH210, Safety data sheet available on request.

2.3. Other hazards

Additional warnings

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Propane-1,2-diol	CAS No.: 57-55-6 EC No.: 200-338-0 REACH: 01-2119456809-23-XXXX Index No.:	1-3%		
2-butoxyethanol	CAS No.: 111-76-2 EC No.: 203-905-0 REACH: 01-2119475108-36-XXXX Index No.: 603-014-00-0	0.1-0.9%	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332	[1]
(2-methoxymethylethoxy)propanol	CAS No.: 34590-94-8 EC No.: 252-104-2 REACH: 01-2119450011-60-XXXX Index No.:	0.1-0.9%		[1]
ammonia%	CAS No.: 1336-21-6 EC No.: 215-647-6 REACH: 01-2119982985-14-XXXX Index No.: 007-001-01-2	0.1-0.9%	Acute Tox. 4, H302 Skin Corr. 1B, H314 STOT SE 3, H335 (SCL: 5.00 %) Aquatic Acute 1, H400 (M=1)	
1,2-benzisothiazol-3(2H)-one;1,2-benzisothiazolin-3-one	CAS No.: 2634-33-5 EC No.: 220-120-9 REACH: 01-2120761540-60-XXXX Index No.: 613-088-00-6	0.01-0.09%	Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Dam. 1, H318 Acute Tox. 2, H330 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411	
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	CAS No.: 55965-84-9 EC No.: 611-341-5 REACH: Index No.: 613-167-00-5	0.001-0.0014%	EUH071 Acute Tox. 3, H301 Acute Tox. 2, H310 Skin Corr. 1C, H314 (SCL: 0.60 %) Skin Irrit. 2, H315 (SCL: 0.06 %) Skin Sens. 1A, H317 (SCL: 0.0015 %) Eye Dam. 1, H318 (SCL: 0.60 %) Eye Irrit. 2, H319 (SCL: 0.06 %) Acute Tox. 2, H330 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100)	

2-methylisothiazol-3(2H)-one	CAS No.: 2682-20-4 EC No.: 220-239-6 REACH: 01-2120764690-50-XXXX Index No.: 613-326-00-9	0.001-0.0014%	Acute Tox. 3, H301 Acute Tox. 3, H311 Skin Corr. 1B, H314 Skin Sens. 1A, H317 (SCL: 0.0015 %) Eye Dam. 1, H318 Acute Tox. 2, H330 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1)
------------------------------	--	---------------	---

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact

If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during transport.

Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact.

Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are

produced. These are:
Carbon oxides (CO / CO₂)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the National Poisons Information Centre (NPIC) on +353 (0) 1 809 256 (24 h service) in order to obtain further advice. Fire fighters should wear appropriate personal protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation, especially in confined areas.
Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.
Keep unauthorized persons away from the spill

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.
See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Smoking, drinking and consumption of food is not allowed in the work area.
See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material

Always store in containers of the same material as the original container.

Storage conditions

No specific requirements

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Propane-1,2-diol

Long term exposure limit (8 hours) (mg/m³): 470 (total (vapour and particulates)) / 10(particulates)

Long term exposure limit (8 hours) (ppm): 150 (total (vapour and particulates))

2-butoxyethanol

Long term exposure limit (8 hours) (mg/m³): 98

Long term exposure limit (8 hours) (ppm): 20

Short term exposure limit (15 minutes) (mg/m³): 246

Short term exposure limit (15 minutes) (ppm): 50

Annotations:

IOELV = Indicative Occupational Exposure Limit Values are health based limits set under the Chemical Agents Directive (98/24/EC).

Sk = Substance, which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body.

(2-methoxymethylethoxy)propanol

Long term exposure limit (8 hours) (mg/m³): 308

Long term exposure limit (8 hours) (ppm): 50

Annotations:

IOELV = Indicative Occupational Exposure Limit Values are health based limits set under the Chemical Agents Directive (98/24/EC).

Sk = Substance, which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body.

2024 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations (2001-2021) and the Safety, Health and Welfare at Work (Carcinogens, Mutagens and Reprotoxic Substances) Regulations (2024).

DNEL

(2-methoxymethylethoxy)propanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	121 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	283 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	37.2 mg/m ³
Long term – Systemic effects - Workers	Inhalation	308 mg/m ³
Long term – Systemic effects - General population	Oral	36 mg/kg bw/day

Propane-1,2-diol

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	10 mg/m ³
Long term – Local effects - Workers	Inhalation	10 mg/m ³
Long term – Systemic effects - General population	Inhalation	50 mg/m ³
Long term – Systemic effects - Workers	Inhalation	168 mg/m ³

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	20 µg/m ³
Long term – Local effects - Workers	Inhalation	20 µg/m ³
Short term – Local effects - General population	Inhalation	40 µg/m ³
Short term – Local effects - Workers	Inhalation	40 µg/m ³
Long term – Systemic effects - General population	Oral	90 µg/kgbw/day
Short term – Systemic effects - General population	Oral	110 µg/kgbw/day

PNEC

(2-methoxymethylethoxy)propanol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		19 mg/L
Freshwater sediment		70.2 mg/kg
Intermittent release (freshwater)		190 mg/L
Marine water		1.9 mg/L
Marine water sediment		7.02 mg/kg
Sewage treatment plant		4.168 g/L
Soil		2.74 mg/kg

Propane-1,2-diol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		260 mg/L
Freshwater sediment		572 mg/kg
Intermittent release (freshwater)		183 mg/L
Marine water		26 mg/L
Marine water sediment		57.2 mg/kg

Sewage treatment plant	20 g/L
Soil	50 mg/kg
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	
Route of exposure:	Duration of Exposure:
Freshwater	3.39 µg/L
Freshwater sediment	27 µg/kg
Intermittent release (freshwater)	3.39 µg/L
Intermittent release (marine water)	3.39 µg/L
Marine water	3.39 µg/L
Marine water sediment	27 µg/kg
Sewage treatment plant	230 µg/L
Soil	10 µg/kg

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

Measures to avoid environmental exposure


No specific requirements.

Individual protection measures, such as personal protective equipment

Generally

Use only CE marked protective equipment.


Respiratory Equipment

Work situation	Type	Class	Colour	Standards	
Where risk assessment shows air-purifying respirators are appropriate.	Combination filter A2P2	Class 2	Brown/White	EN14387	

Skin protection

Recommended	Type/Category	Standards
No special when used as intended.	-	-

Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	0,11-0,14	(> 480 min)	EN374-2	

Eye protection

Type	Standards
------	-----------

Safety glasses with side shields.	EN166
-----------------------------------	-------



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

Clear, Various colours

Odour / Odour threshold

Faint

pH

>8.1

Density (g/cm³)

-

Relative density

1.02

Kinematic viscosity

0.25 cm²/s (40 °C)

Particle characteristics

Does not apply to liquids.

Phase changes

Melting point/Freezing point (°C)

2

Softening point/range (°C)

Does not apply to liquids.

Boiling point (°C)

>42

Vapour pressure

3.2 kPa (20 °C)

Relative vapour density

7.5

Decomposition temperature (°C)

Stable under normal handling and storage conditions.

Data on fire and explosion hazards

Flash point (°C)

Not applicable - the product is not classified as flammable.

Flammability (°C)

The material is not combustible.

Auto-ignition temperature (°C)

Testing not relevant or not possible due to nature of the product.

Lower and upper explosion limit (% v/v)

Not applicable - the product is not classified as flammable.

Solubility

Solubility in water

Partially soluble in cold water.

n-octanol/water coefficient (LogKow)

No relevant or available data due to the nature of the product.

Solubility in fat (g/L)

No relevant or available data due to the nature of the product.

9.2. Other information

Evaporation rate (n-butylacetate = 100)

Not applicable

VOC (g/L)

33

Other physical and chemical parameters

Volume Solids 30.5% +/- 1.0%. Weight Solids 32.0 +/- 1.0%.

Oxidizing properties

Testing not relevant or not possible due to nature of the product.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance	Propane-1,2-diol
Species:	Rat
Route of exposure:	Oral
Result:	22000 mg/kg

Product/substance	Propane-1,2-diol
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	>2000 mg/kg

Product/substance	Propane-1,2-diol
Species:	Rabbit
Route of exposure:	Inhalation
Test:	LC50 (2 hours)
Result:	>317 mg/L

Product/substance	2-butoxyethanol
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	1746 mg/kg

Product/substance	2-butoxyethanol
Species:	Guinea pig
Route of exposure:	Inhalation
Test:	LC0
Result:	>3.1 mg/L

Product/substance	(2-methoxymethylethoxy)propanol
Test method:	OECD 401
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	>4000 mg/kg

Product/substance	ammonia%
Species:	Rat

Route of exposure: Inhalation
Test: LC50 (4 hours)
Result: 980 mg/m³

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

This product contains substances that may trigger an allergic reaction in already sensitized persons.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Due to the viscosity, this product does not present an aspiration hazard.

11.2. Information on other hazards

Long term effects

None known.

Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information

2-butoxyethanol has been classified by IARC as a group 3 carcinogen.

SECTION 12: Ecological information

12.1. Toxicity

Product/substance	Propane-1,2-diol
Species:	Fish, <i>Oncorhynchus mykiss</i>
Duration:	96 hours
Test:	LC50
Result:	40613 mg/L

Product/substance	Propane-1,2-diol
Species:	Daphnia, <i>Ceriodaphnia dubia</i>
Duration:	48 hours
Test:	EC50
Result:	18340 mg/L

Product/substance	Propane-1,2-diol
Species:	Algae, <i>Pseudokirchneriella subcapitata</i>
Duration:	96 hours
Test:	EC50
Result:	19000 mg/L

Product/substance	ammonia%
Species:	Daphnia, <i>Daphnia magna</i>
Duration:	48 hours
Test:	EC50
Result:	0.66 mg/L

Product/substance	ammonia%
Species:	Fish, <i>Gambusia affinis</i>

Compartment: Freshwater
Duration: 96 hours
Test: LC50
Result: 37 ppm

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Test method: OECD 201
Species: Fish, *Oncorhynchus mykiss*
Duration: 96 hours
Test: LC50
Result: 0.22 mg/L

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Test method: OECD 211
Species: *Daphnia*
Duration: 21 days
Test: NOEC
Result: 0.004 mg/L

Product/substance reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Test method: ISO 10253 2006
Species: Algae, *Skeletonema costatum*
Duration: 48 hours
Test: NOEC
Result: 0.00064 mg/L

12.2. Persistence and degradability

Product/substance (2-methoxymethylethoxy)propanol
Conclusion: Readily biodegradable
Test: OECD 301 F

12.3. Bioaccumulative potential

Product/substance Propane-1,2-diol
LogKow: -0.92
Conclusion: -

Product/substance (2-methoxymethylethoxy)propanol
LogKow: 0.004
Conclusion: -

Product/substance ammonia%
Conclusion: Potential for bioaccumulation

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is not covered by regulations on dangerous waste.
Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

EWC code

Not applicable.

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other informatio n:
ADR	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

* Packing group

** Environmental hazards

Additional information

Not dangerous goods according to ADR, IATA and IMDG.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

No special.

Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

Not applicable.

Additional information

Not applicable.

Sources

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H301, Corrosive to the respiratory tract.

H302, Toxic if swallowed.

H310, Fatal if swallowed.

H311, Toxic in contact with skin.

H312, Harmful in contact with skin.

H314, Causes severe skin burns and eye damage.

H315, Causes skin irritation.

H317, May cause an allergic skin reaction.

H318, Causes serious eye damage.

H319, Causes serious eye irritation.

H330, Fatal if inhaled.

H332, Harmful if inhaled.

H335, May cause respiratory irritation.

H400, Very toxic to aquatic life.

H410, Very toxic to aquatic life with long lasting effects.

H411, Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
 ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
 ATE = Acute Toxicity Estimate
 BCF = Bioconcentration Factor
 CAS = Chemical Abstracts Service
 CE = Conformité Européenne (European conformity)
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 CSA = Chemical Safety Assessment
 CSR = Chemical Safety Report
 DMEL = Derived Minimal Effect Level
 DNEL = Derived No Effect Level
 EINECS = European Inventory of Existing Commercial chemical Substances
 ES = Exposure Scenario
 EUH statement = CLP-specific Hazard statement
 EuPCS = European Product Categorisation System
 EWC = European Waste Catalogue
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 GWP = Global warming potential
 IARC = International Agency for Research on Cancer (IARC)
 IATA = International Air Transport Association
 IBC = Intermediate Bulk Container
 IMDG = International Maritime Dangerous Goods
 LogPow = logarithm of the octanol/water partition coefficient
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 OECD = Organisation for Economic Co-operation and Development
 PBT = Persistent, Bioaccumulative and Toxic
 PNEC = Predicted No Effect Concentration
 RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
 RRN = REACH Registration Number
 SCL = A specific concentration limit
 SVHC = Substances of Very High Concern
 STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
 STOT-SE = Specific Target Organ Toxicity - Single Exposure
 TWA = Time weighted average
 UN = United Nations
 UVBC = Unknown or variable composition, complex reaction products or of biological materials
 VOC = Volatile Organic Compound
 vPvB = Very Persistent and Very Bioaccumulative

Additional information

Not applicable.

The safety data sheet is validated by

EcoOnline

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: IE-en