



Gerband 6300 Primer

Gerband Primer 6300 is used for improvement of the adhesive properties of substrates which should be bonded like ber boards, sandy brick and concrete.

- Solvent-free dispersion
- Specially developed for increasing the adhesion of adhesive tapes and adhesives on wood ber boards, sanding masonry, concrete and others, especially in the system with FORTAX® adhesive seals and Gerband adhesive tapes for the airtight building envelope
- Easy and even to apply
- Quick-drying
- Tack-free surface after drying Colour
- Transparent

Application

- Improves the adhesion properties of the substrate to be bonded.
- Solidifies porous or sandy materials.

Application Notes

- Apply at temperatures from +5 °C to +35 °C.
- Drying time approx. 30 min to 60 min.
- Store in dry rooms from +5 °C to +23 °C, protected from UV-radiation.
- Keep out of reach for children!

Processing

- Apply Gerband Primer 6300 on the surface to be bonded.
- Let the primer dry well for further processing -the surface of the applied primer should feel mostly dry.
- Apply several times on difficult substrates, if necessary, and allow to dry well each time.
- Apply the adhesive tape on the treated surface and press firmly at once - please observe the instructions for use of the respective adhesive tape.

Ecology and disposal

- Free of solvents.
- No environmental or indoor toxins.
- Can easily be disposed of with household waste.



Technical Data

Basis	polyacrylate dispersion
Temperature range after application	-20 °C to + 0 °C
Shelf life	in unopened can, 12 months
Typical Consumption Rate (per 1 kg)	
Stone/concrete	approx. 12 m ²
Fireboards	approx. 6 m ²