

BETTER OLA

OptiStep®



U:
1.13
W/m²K

high insulation



easy and quick
installation



high comfort
of use



additional
accessories
available
page 19

3.6
cm

WARRANTY
2
YEARS

Maximum loading	150 kg
Ladder width	38 cm
Tread width	8 cm
Tread length	34 cm
Distance between treads	25 cm
Hatch thickness	3.6 cm
Box height	14 cm
Heat transfer coefficient*	U=1.13W/m ² K

*manufacturer's internal testing for the middle part of the hatch

Hatch

- 3.6 cm thick insulated hatch of sandwich type;
- finished with HDF board white on both sides;
- equipped with a snap lock;
- opened by means of included control rod.

Box

- made of pine wood;
- stiffened in corners by means of a spring catch;
- equipped with seal;

Ladder

- 3-section ladder;
- made of pinewood.

Treads

- treads connected to the strings by means of dovetail joints for increased connection durability;
- equipped with special anti-slipping grooves for extra security.

Available sizes

60x111, 60x120, 60x130, 70x111, 70x120, 70x130 [cm]



Energy-efficiency

3.6 cm thick insulated hatch reduces heat loss.



Perfect tightness

White on the outer side, the hatch matches perfectly with the interior design.



Safety of use

Hatch is equipped with a snap lock which presses the hatch against seals.



Comfort of use

Metal handrail increases comfort and safety of loft ladder use.