



Glidevale Rafter Roll Ventilators

Product Code : RV300 / RV450 / RV600 / RV900

Laid continuously over the rafters before the underlay is fixed, provides a maximum 25 000mm² dependent on eaves ventilation inlet provision. Universal, adjusts for 400 - 600mm rafter centres.

Available in 4 widths: 300mm, 450mm, 600mm and 900mm

RV Rafter Ventilators are designed to ensure a clear air path between roof underlay and insulation at all types of eaves, in accordance with Building Regulations Approved Document C2. They should be installed continuously with FV Fascia Ventilators or SV Soffit Ventilators, to provide a continuous ventilation path from the roof void to the outside without impairing the weatherproof function of the structure, as required by BS 5250. Composition: Manufacture Vacuum-formed black PVC.

Advantages

- Reduce the risk of cold bridging by enabling insulation to be laid right into eaves.
- Independent of SV and FV ventilators, enabling use with any depth of soffit.
- Unique cross strengthening ribs on rafter trays prevent the underlay from sagging and blocking the airflow.
- Quick and easy to install, with no special tools required.
- Do not affect the slating/tiling process.
- Lightweight and durable.
- Suit standard rafter spacings.



Effective coverage per length for rafter spacing:
600mm 6.0m or 10 rafter voids
450mm 6.0m or 13 rafter voids
400mm 6.0m or 15 rafter voids

(Eaves Carrier Tray)
 (Rafter Roll)
 (Overfascia Vent)

