

# TG-15 Fibreglass Mesh

## Reinforcing mesh 165 gr / m<sup>2</sup>.

Component of SempreTherm External Wall Insulation Systems.

Technical Data Sheet  
No. 7.FGM  
12.09.2016

### Characteristics

- alkali-resistant
- slip-proof
- tear-proof
- algae and fungi resistant

### Scope of use

Reinforcing mesh for embedding into reinforced layers made from Sempre Universal TU-200 basecoat in SempreTherm External Wall Insulation Systems. For facades exposed to higher mechanical loads.

### Application

The Basecoat (TU-200) is prepared and is trowel applied to the surface of dry insulation boards at approximately 2 / 3 of the final basecoat thickness. Basecoats requiring the addition of water should be mixed mechanically using a drill and mixer. A 10 mm toothed trowel (held at 45° to the insulation board) is used to leave castellations in the basecoat.

A layer of alkali resistant fibreglass mesh is then applied either vertically or horizontally ensuring the mesh is overlapped at joint by a minimum coverage of 100 mm (overlaps in quoins should be min. 150 mm ). The mesh should be pressed into the basecoat using a notched float so that it is not visible, yet it should not make direct contact with the Insulation. The remaining 1/3 thickness of basecoat is then applied as required to ensure the mesh is completely covered and the required minimum thickness of base coat is achieved. Additional pieces of reinforcing mesh are applied diagonally at the corners of openings to provide the necessary reinforcement in prior to the application of the basecoat. At affected locations apply, install 200 x 300 mm mesh strips at a 45° angle in relation to the lines determined by the reveal embedded into basecoat in accordance with the Certificate holders instructions.

### Storage

In a dry place, upright and free from pressure

### Packaging

Rolls of 1 m width and 50 m length



### Technical data

Base:	glass fabric
Weight:	165 gr / m <sup>2</sup>
Colour:	white
Temperature of application:	from +5 °C to +25 °C
Mesh size:	4 mm x 4 mm
Estimated consumption:	approx. 1,1 m <sup>2</sup> / m <sup>2</sup>
This product is certified by:	
- BBA Agrément Certificate No - 14/5159	
- NSAI Agrément Certificate No - 11/0358	
- European Technical Approval No - 08/0316	

**Should you need support or advice, please consult our advisory service for architects and contractors on the hotline number:**

**Phone: +44 203 637 4495**

**e-mail: [info@innovate-group.co.uk](mailto:info@innovate-group.co.uk)**

The information contained herein, particularly recommendations for the handling and use of our products, is based on our professional experience. As materials and conditions may vary with each intended application, and thus are beyond our sphere of influence, we strongly recommend that in each case sufficient tests are conducted to check the suitability of our products for their intended use. Legal liability cannot be accepted on the basis of the contents of this data sheet or any verbal advice given, unless there is a case of wilful misconduct or gross negligence on our part. This technical data sheet supersedes all previous editions relevant to this product.



UK Distributor: Innovate Group Ltd,  
Suite 314, Sterling House, Langston Road  
Loughton, Essex, IG10 3TS

Phone: +44 203 637 4495  
Email: [info@innovate-group.co.uk](mailto:info@innovate-group.co.uk)  
Web: [www.innovate-group.co.uk](http://www.innovate-group.co.uk)

Manufacturer: Fiberglass Fabrics s.c.  
ul. Torowa 4, 45-073 Opole, Poland  
+48 77 547 19 55, [biuro@fiberglass-fabrics.pl](mailto:biuro@fiberglass-fabrics.pl)