



EVO-STIK FLASHBAND ORIGINAL

Self Adhesive Flashing Tape

DESCRIPTION

Evo-Stik Flashband Original is a self adhesive sealing bitumen strip which bonds instantly to provide a permanent watertight seal in all climates. Evo-Stik Flashband Original is easily applied using hand pressure and a seam roller, with no requirement for special equipment for cutting, forming or fixing. Before using this product refer to the relevant Health & Safety Data Sheet.

FEATURES

- Superior high temperature performance characteristics
- Quick and easy application
- Bonds to a wide range of building materials
- Cost effective method of flashing, sealing and repair
- Provides lasting protection in all climates
- Safe in application, storage and transport
- Lasts up to 15 years

USES

- Bonds to most building materials including brick, masonry, slates, concrete roof tiles, wood, metal, concrete, terracotta tiles, glass, roofing felt, rigid plastics etc
- Applications include a large variety of original construction and maintenance situations including repairing lead flashing, sealing valley gutters, mending leaks in drain pipes and guttering, greenhouse repairs, protecting glazing bars, protecting insulation for pipes and tanks, repairing roofing felt joints on flat roofs

PRODUCT CHARACTERISTICS

Colour	Grey finish
Form	Resin modified bituminous mastic in roll form. Adhesive surface is protected by a removable release backing
Composition	Resin modified bituminous mass

Weight	1.6kg per square metre	
Product Codes	Grey Finish – 3.75 metre rolls	
	194601	75mm x 8 rolls
	194656	100mm x 6 rolls
	194717	150mm x 4 rolls
	194755	225mm x 4 rolls
	194809	300mm x 2 rolls
	Grey Finish – 10 metre rolls	
	196506	50mm x 6 rolls
	200005	75mm x 4 rolls
	205000	100mm x 3 rolls
	210004	150mm x 2 rolls
	215009	225mm x 2 rolls
	220003	300mm x 1 roll
	225008	450mm x 1 roll
	228504	600mm x 1 roll
Shelf life/ storage	One year from date of manufacture when stored in original unopened packaging in a cool, dry place within the temperature range +5°C to +25°C	

TYPICAL PERFORMANCE DATA (APPROX.)

Temperature Resistance	-10°C to +100°C
Application Temperature	+5°C to +30°C. NB in cold weather, (below +15°C) application may be made easier by warming the surfaces and storing Flashband in a warm place prior to use.
Life Expectancy	Special grey lacquer finish, at least 15 years

DIRECTIONS FOR USE

IMPORTANT

Before using Evo-Stik Flashband Original refer to the relevant Health & Safety Data Sheet, available at www.bostik.co.uk.